

GTM México Products and Services
 S.A. de C.V.
 SDS
 Av. Gustavo Baz Prada No. 3967
 54030 TLANEPANTLA DE BAZ CP.
 MEXICO

Certificate of Analysis

Your order no./date
 4691 / 01.03.2022
 Delivery item/date
 36935858 000001 / 26.09.2022
 Order no./date
 240001450 000001 / 01.03.2022
 Customer no.
 7250020630

Product : 872-2010 COLORTREND® YELLOW C9
 Material no. : 99008978
 Batch : 1082090703
 Standard : 1091061615
 Production date : 13.09.2022

Property	Test method	Unit	Value	min.	max.
Viscosity - Brookfield 4@20	STM/4	cP	1000	1000	3000
PH	STM/3		8.6	8.0	10.0
Grind (µm)	STM/2	µm	20	0	20
SG (50:50 WATER)	STM/7		1.30	1.00	1.30
DE (strong shade)	STM/1 & 17		0.41		1.00
DE (weak shade)	STM/1 & 17		0.24		0.60
DL (weak shade)	STM/1 & 17		0.29	-0.40	0.40
Da (weak shade)	STM/1 & 17		0.25	-0.40	0.40
Db (weak shade)	STM/1 & 17		0.14	-0.40	0.40
DE Rub - Internal Base 1 (weak shade)	STM/1 & 17		0.69		0.80
Colour Strength (weak shade)	STM/1 & 17		98.3	98.0	102.0

DISCLAIMER: This certificate has been prepared with care and the best of our knowledge as part of the quality assurance system from Chromaflo Technologies Corporation. It is provided for informational purposes only and does not relieve our customers of their obligation to perform proper incoming inspections upon receipt or establish any warranty to third parties to whom it might be passed on. Furthermore, it is solely the customer's responsibility to determine the suitability of the product for its intended use. Chromaflo Technologies Corporation warrants that the product described herein fully meets its sales specification. THIS WARRANTY IS GIVEN IN LIEU OF ALL OTHER WARRANTIES OR REPRESENTATIONS, WRITTEN OR ORAL, STATUTORY, EXPRESSED OR IMPLIED, AND THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE ARE EXPRESSLY DISCLAIMED. Before using any chemical, read its label and material safety data sheet.